

**Model: [660](#)  
15 FRAME PLUNGER PUMP**

**Specs**

<b>Max Flow:</b>	10 gpm
<b>Min Pressure:</b>	100 psi
<b>Max Pressure:</b>	3000 psi
<b>Inlet Port Size:</b>	3/4"NPT(F)
<b>Discharge Port Size:</b>	1/2"NPT(F)
<b>RPM:</b>	1429
<b>Drive Type(s):</b>	Belt
<b>Material:</b>	Brass (BB)

**Description:**

This is a triplex [three plunger rods] positive displacement, reciprocating, plunger pump, constructed of a forged brass manifold, 304SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. [see also 316SS models]

**Datasheet:** [660-661D-661C Data Sheet](#)

**Service Manual:** [5-15 Frame Plunger Service Manual](#)

**Accessories:**


Oil



[6107](#)

Crankcase Oil

Regulator



[7014](#)

Pressure Regulator

Pressure Gauge



[6089](#)

Pressure Gauge

Pulsation Dampener



[6029](#)

Prrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube

Inlet Filter



[7105.5](#)

Inlet Filter

Flexible Inlet Hose



[990840](#)

Flexible Inlet Hose

### Flexible Discharge Hose



[990836](#)

Flexible Discharge Hose

### LPS Monitors



[30664](#)

LPS Monitor



[30664.120AC](#)

LPS Monitor

### Other



[34334](#)

Oil Drain Kit