

POSEIDON 6



Nilfisk
ALTO
works for you

POSEIDON 6

Industrial cold water pressure washer

Powerful Cleaning - Pressure levels of up to 250 bar provide heavy duty cleaning bringing working time down considerably.

Easy to use - Simple to operate with large clear controls, large manoeuvrable rear wheels and single front castor with brake; making the machine easy to manoeuvre & stable even on uneven ground.

New NA6 pump - This new heavy duty 4 piston pump is designed around the C3 pump concept (double roller bearings, long lifetime and high inlet temp) but with a wider span of performance capabilities.

Easy access - Easy to open cabinet for quick & simple access for service and greater accessibility to service parts, saving time & costs.

Ergo 2000 Spray Gun - The ultimate in ergonomics, user friendliness and adaptability. The spray gun has a 360 degree swivel reducing fatigue, plus with Ergo coupling just one click and the hose is connected for quick set up.

Accessory Storage- 2 lance holders ensure easy and convenient storage of accessories.

TECHNICAL DATA	POSEIDON 6-64 FA	POSEIDON 6-65 FA	POSEIDON 6-79 FA	POSEIDON 6-61 FFA
Pump pressure (bar/MPa)	250/25	180/18	170/17	100/10
Cleaning impact (kg/force)	6.4	6.5	7.9	6.1
Water flow Qmax/Qiec (l/h)	1100/1000	1300/1200	1600/1500	1600/1500
Max. inlet temperature (°C)	80	80	80	80
Pump (RPM)	1450	1450	1450	1450
Dimensions L x W x H (mm)	775 x 570 x 1020	775 x 570 x 1020	775 x 570 x 1020	775 x 570 x 1020
Weight (kg)	89	86	89	80
Power consumption (kW)	8.5	7.4	8.8	5.7
Voltage/phase/frequency/current (V/~/Hz/A)	400/3/50/15	400/3/50/14.5	400/3/50/16	400/3/50/10
EI cable (m)	8	8	8	8
Suction height dry (m)	1	1	1	1
FEATURES				
Pistons / number of pistons	Ceramic / 4	Ceramic / 4	Ceramic / 4	Ceramic / 4
Automatic start/stop	•	•	•	•
Low pump oil safety	•	•	•	•
Water flow regulation	•	•	•	•
Additional hose and rotary jet lance				
Detergent tank (l)	2 x 2.5	2 x 2.5	2 x 2.5	2 x 2.5
Hose reel				
STANDARD EQUIPMENT				
HP hose (DN10)	• [10 m]	• [10 m]	• [10 m]	• [10 m]
Ergo 2000	•	•	•	•
Ergo 3000				
Ergo coupling	•	•	•	•
Water inlet coupling	•	•	•	•
Hose reel				
Tornado Plus lance without HP nozzle	•	•	•	•
TurboHammer Plus lance with HP nozzle				
Tornado Plus nozzle	•	•	•	•
VERSIONS AVAILABLE				
ITEM NO.	FA / FAXT	FA / FAXT	FA / FAXT	FFA
	107146751 / 107146758	107146752 / 107146759	107146755 / 107146761	107146763

FAXT: Flow activated, time delayed shutdown, comes with hose reel, additional hose & rotary jet lance.

FFA: Flow activated, time delayed shutdown. Food industry suitable with stainless steel frame and grey non marking hose and wheels.

FA: Flow activated, time delayed shutdown

DETERGENT APPLICATION



The 2 x 2.5 l tanks are easily removable for emptying and filling. It is also easy to see the level of detergent remaining in each tank, thus allowing the user to pre-fill enough detergent before leaving for the work place.

TRANSPORTABILITY



The foldable handle reduces the storage or transport space required in a vehicle or workshop. A vertical position for the handle gives optimum balance for lifting with a crane or loader

Optional Accessories (see product catalogue for further accessories)



Crane Roundsling

Ideal for easily manoeuvring machines using cranes or loaders



Drain pipe cleaner

Clears blocked drains with ease, available with 10 or 20m hose



Foam lance

Used together with Foam injector & by-pass for cleaning surfaces & equipment



Vehicle Accessories

Under carriage lances for hard to reach areas of stubborn dirt

Distributed by:

No claims can be made on the basis of information or illustrations contained in literature. Subject to alteration of technical data, design and equipment

www.nilfisk-alto.co.uk
www.nilfisk-alto.ie

Nilfisk
ALTO
works for you