

Neutral Universal cleaning agent.

A liquid, neutral, mildly foaming cleaning agent for removing oily and greasy dirt as well as dust, soot and various other kinds of deposits from all water-resistant surfaces.

Effective against: Grease ; Oil ; Soot ; Dirt and dust

Field of use:

- Vehicle cleaning operations: for cleaning the outside of vehicles when it is important to get satisfactory results with untrained cleaning operators.
- Industrial and Public Facilities: where floor cleaning operations are necessary to remove grease or oil from hard floor surfaces.
- Manufacturing facilities: where grease or oil must be removed from machinery or workpieces.

Also useful in the equipment maintenance areas of these facilities, for light degreasing work.

Product benefits:

- Effective, and a time-saver because Universal has a powerful cleaning action, but is gentle to surfaces being cleaned.
- Economical to use because it is effective in small concentrations.
- User and Environmentally friendly due to the high degree of biodegradability, and because it can be separated in recycling systems.
- Free of dyes and aromatic substances that are normally prohibited in Food and Cosmetic industries.
- Suitable for use in foodstuffs industries (Labor Dr. Boehm, Munich)

pH value: 7

Notes:

UN Number : na ; Class / Packing Group : na

Various cleaning tasks on a wide range of particularly delicate surfaces in trade and industry.

Application:

- High Pressure Washers: Put Universal in the machine detergent tank undiluted, and set the detergent injector for 2 – 7%, as required by the degree of soiling. Always rinse thoroughly after cleaning operations.
- Floor Care machines: For maintenance cleaning operations, dilute Universal between 1:100 (1%) and 1:20 (5%), depending on the degree of soiling. Apply and remove normally.
- Pre-spraying application: Dilute between 1:50 (2%) and 1:10 (10%), and spray directly on the soiled surface or object. After allowing Universal to work (3-10 minutes), rinse the surface thoroughly with clean water.
- Do not use on hot, painted surfaces, and do not allow Universal to dry on the surface.

- Standard equipment

- Standard equipment



Picture shown may not represent model quoted

Model	ALTO AL 322 220 KG	AL 322 1000 KG LEIHCONTA	ALTO UNIVERSAL 10 L
Ref. no.	8352	80782	80930

Technical specifications

Packaging	10 L
Ph value	7 (1% solution)

Model	ALTO UNIVERSAL 25 L	NILFISK-ALTO UNIVERSAL 4 X 2.5 L
Ref. no.	81225	25000213

Technical specifications

Packaging	
Ph value	

● Standard equipment, ○ Supplementary accessories, □ Mountable equipment

● Standard equipment, ○ Supplementary accessories, □ Mountable equipment

