

MC 8P

# Powerful high flow cleaning





For tough use in:

- agriculture
- food industry
- vehicle & transport
- building & construction

# Robustness and high power

Agriculture, transport, construction and food industry have a growing need for high water flow combined with high pressure.

The Nilfisk MC 8 line offers optimal performance in one big, tough package for even the hardest cleaning tasks. The advantages of high water flow and high pressure, allowing both cleaning of intense dirt and flushing and rinsing of large quantities of loose dirt.

## Powerful Cleaning

Pressure levels of up to 180 bar and water flow of up to 2500 l/h depending upon the models means you can cut into even ingrained dirt or flush away masses of loose dirt, bringing working time down considerably. MC 8P can also be used by 2 people at the same time thanks to the high water flow.

## Easy to Use

As for all the Nilfisk pressure washers, focus has been on ergonomics and ease of use. The MC 8P is a simple machine to use – quick to install, quick to change accessories and easy to move around.

## Features for your MC 8P

The MC 8P is available with steel or stainless steel frame for use in even the most aggressive environments. The frame is robust, stable and protects all vital components. Pump oil sight makes it possible easily to check the oil level for the pump without dismantling the machine. The time delayed start stop system protects the motor and reduces noise levels during pauses.



Full ceramic piston pumps are used in order to offer long working life. The motor is of course, slow running 1450 rpm.



MC 8P is quick and easy to install. With the professional inlet coupling it could not be easier connecting the hose to the machine.



2 lance holders ease storage of additional accessories.



The big, wide pneumatic wheels make the MC 8P very stable and also easy to move around on uneven ground. The parking brake ensures that the machine can be used in all security.

# The cool facts for the MC 8P

- Tough steel or stainless steel frame variants
- Slow running 1450 rpm motors with low noise level
- Ceramic pistons for longer working life
- Simple and easy to use
- Parking brake
- 15 m HP hose



## TECHNICAL SPECIFICATIONS

Description	MC 8P-160/2500	MC 8P-160/2500 ST	MC 8P-180/2100
Item no.	301002535	301002619	301002534
Pump pressure (bar/MPa)	160/16	160/16	160/16
Cleaning impact (kg/force)	12.5	12.5	12.5
Water flow Qmax/Qiec (l/h)	2500/2450	2500/2450	2100/2050
Max inlet temperature (°C)	50	50	50
Dimensions LxWxH (mm)	900x660x910	900x660x910	900x660x910
Weight (kg)	130	130	130
Power consumption (kW)	14.5	14.5	14
Voltage/phase/frequency/current (V/~/HZ/A)	400/3/50/24.9	400/3/50/24.9	400/3/50/24
El cable (m)	5	5	5
Ceramic pistons	3	3	3
Suction height dry (m)	1.5	1.5	1.5
Suction height - primed (m)	2.5	2.5	2.5
Nozzle size	.1590	.1590	.1200
<b>Features:</b>			
Stainless steel frame		•	
SilentPower - 1450 rpm motor	•	•	•
Parking brake	•	•	•
Pneumatic wheels	•	•	•
Automatic on/off and delayed action	•	•	•
<b>Standard equipment:</b>			
Ergo coupling kit	101119496	101119496	101119496
Hose liner 20 R1	6577	6577	6577
Hose DN10 15m 2W 3/8X3/8			1402064
15 m 2 Wire hose 1/2 DN12	4810213	4810213	
Ergo standard w. hose swivel			106403122
Spray handle w. swivel lock	106402190	106402190	
Tornado Plus Lance 1120 Bendt w/o nozzle	106403010	106403010	106403010
Nozzle 1200 Indication ring Caramelle			101119758
Tornado Plus Nozzle 1590 1/8-27NPT	301150004	301150004	

### Nilfisk Ltd

Nilfisk House · Bowerbank Way · Gilwilly Industrial Estate · Penrith · Cumbria · CA11 9BQ  
 Tel: 01768 868995 (UK) · 01 2943838 (IE)  
 Email: mail.uk@nilfisk.com (UK) · info.ie@nilfisk.com (IE)  
 www.nilfisk.co.uk · www.nilfisk.ie