


BENZ



PETROL
MOTOR



BENZ-C H1811Pi P



Extension P70
Code LCPR 40013



Flexible hose 10 m
Code TBAP 25324



Handgrip
Code IPPR 89429



Nozzle for lance
Code UGLN 05199 (IDAF 40356 - IDAF 40358)
Code UGLN 49990 (IDAF 40352 - IDAF 40353 - IDAF 40354 - IDAF 40355)
Code UGLN 49995 (IDAF 40357 - IDAF 40359)



BENZ-C H2013Pi P



BENZ-C L2021Pi P



BENZ-C L DL2217Pi P



The anti-vibration coupling between the pump and engine extends the working life of the components and simplifies maintenance.



The HS 2620 has a thermostatic valve to protect the pump from possible overheating of the water.



Honda GX air-cooled 4-stroke petrol engines with overhead valves.



L versions are fitted with a reduction gear in oil bath to extend the working life of the pump.



Multipurpose valve:
- Easy Start: to start the motor effortlessly.
- Thermostatic valve: to protect the pump from possible overheating.
- By Pass
- Pressure regulation: to adjust pressure to the surface.

Technical characteristics

BENZ-C H1811Pi P

- THERMOSTATIC valve.
- 280 mm dia. wheels.

BENZ L

- Motor revolutions reduction gear.

ALL OTHERS MODELS

- H.P. crankshaft pump with brass head and ceramic pistons.
- Petrol motors, Honda GX serie, air-cooled 4-stroke overhead valves, manual start and low oil sensor.

- THERMOSTATIC valve and EASY START.
- DL models are equipped with hydraulic decelerator for reduction of motor revolutions during By Pass phase, which allows to reduce consumptions, noise and to increase mechanical components working life.
- Grab bar and tubular steel bumper with rests for lance or gun.
- Steel supporting structure designed to absorb all motor vibrations.
- Pressure adjustment.
- Low pressure detergent delivery with control on lance.
- 315 mm dia. wheels.

Code	Model	Remote control	Pressure (bar)	Flow rate (l/h)	Motor type	Motor (Hp)	RPM	Detergent tank (l)	Weight (Kg)	Dimensions (cm)
IDAF 40352	BENZ-C H1811Pi P	By Pass	30-180	330-660	GX 200	6,5	3600	-	40,2	86x56x54
IDAF 40353	BENZ-C H2013Pi P	By Pass	30-200	400-800	GX 270	9,0	3600	-	62	105x66x75
IDAF 40354	BENZ-C H2515Pi P	By Pass	30-250	450-900	GX 390	13	3600	-	67,2	105x66x75
IDAF 40355	BENZ-C H DL2515Pi P	By Pass	20-250	450-900	GX 390	13	3600	-	68	105x66x75
IDAF 40356	BENZ-C L2216Pi P	By Pass	30-220	500-1000	GX 390	13	1500	-	74	105x66x75
IDAF 40357	BENZ-C L2021Pi P	By Pass	30-200	630-1260	GX 390	13	1500	-	74	105x66x75
IDAF 40358	BENZ-C L DL2217Pi P	By Pass	30-220	500-1000	GX 390	13	1500	-	74,8	105x66x75
IDAF 40359	BENZ-C L DL2021Pi P	By Pass	30-200	630-1260	GX 390	13	1500	-	75,4	105x66x75

Recommended optional accessories



Flexible hose
15 m Code TBAP 40062
20 m Code TBAP 44379



Hose couplings
Code RCIN 10810



Lance with double
nozzle holder
Code LCPR 24906



Mudguard lance
Code LCPR 29360



Double lance
30 cm Code LCPR 12981
50 cm Code LCPR 12982
70 cm Code LCPR 12983



Sandblaster kit
Code LCPR 14858



Hose reel
Code KTRI 37674



Drain Kit 5/16
10 m Code TBAP 23853
20 m Code TBAP 24406

